115,0 g


3,801

20,0 kg









basic data

weight

Weight category

volume to rim

		SI				
	•		 •		•	

without lid

D1 239,0 x 179,0 mm/inch D2 226,0 x 166,0 mm/inch 203,0 x 143,0 mm/inch D3 159,0 mm/inch Н

tolerances

dimensions	±1mm/in
Weight tolerance	±5%

Possible combinations


top load performance

no handle

handle	Description		weight		
	metal handle		20,0 g		
	plastic handle		8,0 g		
lid	Туре	Description		stacking height two fold:	each further:
	standard	DETO 35 P		306,0 mm/inch	146,0 mm/inch
	shaker lid	DETO 35 PR		306,0 mm/inch	146,0 mm/inch
decoration	Method of decoration	height:		width:	median breadth:
	Digital	110,0 mm/inch		580,0 mm/inch	0,0 mm/inch
	IML	139,28 mm/inch		577,56 mm/inch	
	Offset	110,0 mm/inch		565,0 mm/inch	580,0 mm/inch

Logistics (standard view)

Pallet	EUP (Europallet)
Width	80 cm (31,5´´)
Length	120 cm (47,24´´)
Height	2,20 m
Quantity per pallet	1400
Quantity per layer	20



material

Description	Labelling	Recyclinacode

100% Virgin material









misc.

All deliveries are subject to our General Terms and Conditions of Delivery. With respect to possible tolerances, deformations and ink adhesion of the design, express reference is hereby made to our Technical Guidelines, which shall also form an integral part of the content of any delivery transaction. In our Technical Guidelines you will also find details referring to strictest quality and hygiene standards, storage, filling and performance requirements as well to applications and transport. Verbal statements regarding technical data or attributes of our products shall always be limited to the scope that we recommend. Our terms and Conditions of Delivery and Technical Guidelines may be available. For technical reasons, the product image may deviate from the actual item. Technical modifications reserved.





basic data dimensions tolerances

Weight category	Е
weight	35,0 g
displaced volume	0,40

DI	237,6 x 177,6 mm/inch
Н	14,8 mm/inch

dimensions ± 1 mm/in/ Weight tolerance ± 5 %

Possible combinations

bucket

JETO 35 P JETO 45 P






decoration	Method of decoration	height:	width:
	IML	195,00 mm/inch	140,00 mm/inch
	Offset	110.0 mm/inch	165.0 mm/inch

Logistics (standard view)

Pallet	EUP (Europallet)
Width	80 cm (31,5 ´ ´)
Length	120 cm (47,24´´)
Height	2,20 m
Quantity per pallet	5400
Quantity per layer	20



material

Description	Labellina	Recyclinacode

100% Virgin material









misc.

All deliveries are subject to our General Terms and Conditions of Delivery. With respect to possible tolerances, deformations and ink adhesion of the design, express reference is hereby made to our Technical Guidelines, which shall also form an integral part of the content of any delivery transaction. In our Technical Guidelines you will also find details referring to strictest quality and hygiene standards, storage, filling and performance requirements as well to applications and transport. Verbal statements regarding technical data or attributes of our products shall always be limited to the scope that we recommend. Our terms and Conditions of Delivery and Technical Guidelines may be available. For technical reasons, the product image may deviate from the actual item. Technical modifications reserved.





basic data dimensions tolerances

Weight category	Е	DI	236,8 x 176,8 mr
weight	37,0 g	Н	14,8 mm/inch
displaced volume	0,40		

nm/inch dimensions ±1 mm/inch Weight tolerance ±5 %

Possible combinations

bucket

JETO 35 P JETO 45 P






decoration	Method of decoration	height:	width:
	IML	195,00 mm/inch	140,00 mm/inch
	Offset	110.0 mm/inch	165.0 mm/inch

Logistics (standard view)

Pallet	EUP (Europallet)
Width	80 cm (31,5´´)
Length	120 cm (47,24´´)
Height	2,20 m
Quantity per pallet	4800
Quantity per layer	20



material

Description Labelling	Recyclingcode
-----------------------	---------------

100% Virgin material









misc.

All deliveries are subject to our General Terms and Conditions of Delivery. With respect to possible tolerances, deformations and ink adhesion of the design, express reference is hereby made to our Technical Guidelines, which shall also form an integral part of the content of any delivery transaction. In our Technical Guidelines you will also find details referring to strictest quality and hygiene standards, storage, filling and performance requirements as well to applications and transport. Verbal statements regarding technical data or attributes of our products shall always be limited to the scope that we recommend. Our terms and Conditions of Delivery and Technical Guidelines may be available. For technical reasons, the product image may deviate from the actual item. Technical modifications reserved.