



Technical specification bucket

JET 22 P

Jokey Euro Tainer Profi



dimensions


D1: 201,5 mm

D2: 184,0 mm

D3: 171,0 mm

H:* 104,0 mm

*Height without lid



basic data

volume to rim: 2,50 l
weight: 77,0 g
weight group: E

handle types

metal handle 14,0 g
plastic handle 9,0 g
belt handle -
no handle +
body grip -
roller grips -

tolerances

dimensions: +/- 1 mm
volume/weight: +/- 5 %

decoration

height:
width:
median breadth:

Digital

0,0 mm
0,0 mm
0,0 mm

IML

85,64 mm
558,31 mm

offset

55,0 mm
550,0 mm
562,0 mm

lid	DET 200 P	FDET 200 P	FDET 200 P	DET 200 PR
	standard	sealing lid	sealing lid	shaker lid
stacking height two fold:	199,0 mm	215,0 mm	215,0 mm	0,0 mm
each further:	94,0 mm	105,0 mm	105,0 mm	0,0 mm

logistic


Max. compression for standard lid at 20°C on the lowest pail: 22,00 kg

pieces per pallet

bucket 760
pallet height 1,20 m
layer quantities: 24

EUP (Europallet)

80 cm (31,5'') x 120 cm (47,24'')



material



QM / certificates

You can download our current certificates on www.jokey.com.

misc.

All deliveries are subject to our General Terms and Conditions of Delivery. With respect to possible tolerances, deformations and ink adhesion of the design, express reference is hereby made to our Technical Guidelines, which shall also form an integral part of the content of any delivery transaction. In our Technical Guidelines you will also find details referring to strictest quality and hygiene standards, storage, filling and performance requirements as well to applications and transport. Verbal statements regarding technical data or attributes of our products shall always be limited to the scope that we recommend. Our terms and Conditions of Delivery and Technical Guidelines may be available. For technical reasons, the product image may deviate from the actual item. Technical modifications reserved.



Technical specification lid DET 200 P



dimensions

D1: 197,0 mm
H: 12,0 mm

basic data

displaced volume:: 0,30 l
weight: 25,0 g
weight group: E

tolerances

dimensions: +/- 1 mm
volume/weight: +/- 5 %

decoration

Diameter

IML

175,00 mm

offset

145,0 mm

bucket

JET 10 P



JET 22 P



JET 25 P



JET 30 P



JET 34 P



JET 34 PC



JET 38 P



JET 38 PC




logistic

pieces per pallet

lid 4560
pallet height 1,20 m
layer quantities: 24

EUP (Europallet)

80 cm (31,5'') x 120 cm (47,24'')



material



QM / certificates

You can download our current certificates on www.jokey.com.

misc.

All deliveries are subject to our General Terms and Conditions of Delivery. With respect to possible tolerances, deformations and ink adhesion of the design, express reference is hereby made to our Technical Guidelines, which shall also form an integral part of the content of any delivery transaction. In our Technical Guidelines you will also find details referring to strictest quality and hygiene standards, storage, filling and performance requirements as well to applications and transport. Verbal statements regarding technical data or attributes of our products shall always be limited to the scope that we recommend. Our terms and Conditions of Delivery and Technical Guidelines may be available. For technical reasons, the product image may deviate from the actual item. Technical modifications reserved.

Please find further Information at www.jokey.com or via email info@jokey.com

Date: 07.12.2020 rev. 3.0



Technical specification lid

FDET 200 P



dimensions

D1: 196,0 mm
H: 17,2 mm

basic data

displaced volume:: 0,00 l
weight: 28,0 g
weight group: F

tolerances

dimensions: +/- 1 mm
volume/weight: +/- 5 %

decoration

Diameter

IML

175,00 mm

offset

0,0 mm

bucket

JET 10 P



JET 22 P



JET 25 P



JET 30 P



JET 34 P



JET 34 PC



JET 38 P



JET 38 PC




logistic

pieces per pallet

lid 4560
pallet height 1,20 m
layer quantities: 24

EUP (Europallet)

80 cm (31,5'') x 120 cm (47,24'')



material



QM / certificates

You can download our current certificates on www.jokey.com.

misc.

All deliveries are subject to our General Terms and Conditions of Delivery. With respect to possible tolerances, deformations and ink adhesion of the design, express reference is hereby made to our Technical Guidelines, which shall also form an integral part of the content of any delivery transaction. In our Technical Guidelines you will also find details referring to strictest quality and hygiene standards, storage, filling and performance requirements as well to applications and transport. Verbal statements regarding technical data or attributes of our products shall always be limited to the scope that we recommend. Our terms and Conditions of Delivery and Technical Guidelines may be available. For technical reasons, the product image may deviate from the actual item. Technical modifications reserved.

Please find further Information at www.jokey.com or via email info@jokey.com

Date: 07.12.2020 rev. 3.0



Technical specification lid

FDET 200 P



dimensions

D1: 196,0 mm
H: 17,2 mm

basic data

displaced volume:: 0,00 l
weight: 25,0 g
weight group: E

tolerances

dimensions: +/- 1 mm
volume/weight: +/- 5 %

decoration

Diameter

IML

175,00 mm

offset

0,0 mm

bucket

JET 10 P



JET 22 P



JET 25 P



JET 30 P



JET 34 P



JET 34 PC



JET 38 P



JET 38 PC




logistic

pieces per pallet

lid 4560
pallet height 1,20 m
layer quantities: 24

EUP (Europallet)

80 cm (31,5'') x 120 cm (47,24'')



material



QM / certificates

You can download our current certificates on www.jokey.com.

misc.

All deliveries are subject to our General Terms and Conditions of Delivery. With respect to possible tolerances, deformations and ink adhesion of the design, express reference is hereby made to our Technical Guidelines, which shall also form an integral part of the content of any delivery transaction. In our Technical Guidelines you will also find details referring to strictest quality and hygiene standards, storage, filling and performance requirements as well to applications and transport. Verbal statements regarding technical data or attributes of our products shall always be limited to the scope that we recommend. Our terms and Conditions of Delivery and Technical Guidelines may be available. For technical reasons, the product image may deviate from the actual item. Technical modifications reserved.

Please find further Information at www.jokey.com or via email info@jokey.com

Date: 07.12.2020 rev. 3.0



Technical specification lid DET 200 PR



dimensions

D1: 197,0 mm
H: 11,8 mm

basic data

displaced volume:: 0,30 l
weight: 25,0 g
weight group: E

tolerances

dimensions: +/- 1 mm
volume/weight: +/- 5 %

decoration

Diameter

IML

175,00 mm

offset

145,0 mm

bucket

JET 22 P



JET 25 P



JET 30 P



JET 34 P



JET 34 PC



JET 38 P



JET 38 PC




logistic

pieces per pallet

lid 4560
pallet height 1,20 m
layer quantities: 24

EUP (Europallet)

80 cm (31,5'') x 120 cm (47,24'')



material



QM / certificates

You can download our current certificates on www.jokey.com.

misc.

All deliveries are subject to our General Terms and Conditions of Delivery. With respect to possible tolerances, deformations and ink adhesion of the design, express reference is hereby made to our Technical Guidelines, which shall also form an integral part of the content of any delivery transaction. In our Technical Guidelines you will also find details referring to strictest quality and hygiene standards, storage, filling and performance requirements as well to applications and transport. Verbal statements regarding technical data or attributes of our products shall always be limited to the scope that we recommend. Our terms and Conditions of Delivery and Technical Guidelines may be available. For technical reasons, the product image may deviate from the actual item. Technical modifications reserved.

Please find further Information at www.jokey.com or via email info@jokey.com

Date: 07.12.2020 rev. 3.0